



## HOT DIPPED GALVANIZED – CULVERT

**Coating Weights:** 2 oz/ft<sup>2</sup> and 4 oz/ft<sup>2</sup> available.

**Options:** Chemically Treated, TRENCHCOAT™ Dow Protective Film, and Stenciled (One Side, 5-Foot Repeat, Nominal Gauge). Note: TRENCHCOAT™ is a registered trademark of the Dow Chemical Company.

**Size Range, Inches:** Coated edges standard unless specified end use is helical welded culvert. Cut length culvert sheets are available through an outside processor. Please inquire.

**Coil ID:** 24" Available, 20" ID is available for gages 18 and 20.

**Coil Size:** 72" OD, 50,000# maximum coil weight.

**Corrugated Cut Length Sheets:** Width: 25 ½", Length: 60" to 384", Corrugation: 2-2/3" x ½".

**Applicable Specifications:** AASHTO M-218, AASHTO M-246, ASTM A742, ASTM A929.

## HOT DIPPED GALVANIZED - CULVERT

| Gage Number | Min Thickness * | Max Thickness * | Max Width       |
|-------------|-----------------|-----------------|-----------------|
| 8           | 0.159"          | 0.168"          | 48" HR Base     |
| 10          | 0.129"          | 0.138"          | 48" HR Base     |
| 12          | 0.101"          | 0.109"          | 48" HR Base     |
| 14          | 0.072"          | 0.079"          | 48" HR Base     |
| 16          | 0.057"          | 0.064"          | 34 1/8" HR Base |
| 16          | 0.057"          | 0.064"          | 48" CR Base     |
| 18          | 0.046"          | 0.052"          | 48" CR Base     |
| 20          | 0.036"          | 0.040"          | 48" CR Base     |

**Notes:** \* Thickness applies to 2 oz product. For 4 oz product, add 0.003".

Available as coils or corrugated cut length sheets.